



- Intel® Core™ i5-1145G7e 2,4Ghz
- 15.6" Projected Capacitive Multitouch Display (PCAP)
- Aluminum
- Made in Spain
- Fanless compact design



Intel®
Processors



Touch
Technology



Efficient Power
Consumption




Double
Display

CPU boards with latest generation Intel® Processors, fanless, low power consumption and exceptional performance.
Manufactured in Aluminium.
Projected Capacitive Multitouch sensor (PCAP).



Dimensions



Specifications

Display

| | |
|------------------|--|
| Touch technology | Projected Capacitive MultiTouch (PCAP) |
| Inches | 15,6" |
| Format | 16:9 |
| Resolution | 1920 x 1080 |
| Backlight | LED |
| Brightness | 450 cd/m2 |
| Ratio contrast | 800:1 |
| Angle vision | 160/160 |
| LED Life Time | 50.000 h |

System

| | |
|------------|--|
| CPU | Intel® Core™ i5-1145G7e (11th Generation) 2,4Ghz |
| Memory | DDR4 2Gb Scalable a 64Gb |
| Hard Drive | 120/240/480Gb SSD M.2 NVMe. 500Gb/1Tb SATA. |
| Graphics | Intel® HD Graphics |
| Chipset | Intel® Tiger Lake i5-1135G7 SoC |
| OS | Win10 Pro / Win10 IoT Enterprise / Linux |

Input / Output

| | |
|--------------|--|
| USB Ports | 4 x USB3.2 (Gen.2) |
| Serial Ports | - |
| Ethernet | 2 x Intel® Giga Ethernet |
| Video | 2 x HDMI / 2 x DP |
| Audio | 1 x Audio output / 1 x Microphone |
| Expansión | 1 x M.2 E-key (2230) USB2.0 / PCIe1 interface support CNVi |

Mechanical

| | |
|------------|-------------------|
| Dimensions | 393 x 243 x 64 mm |
| Weight | 4,3 kg |
| Mount | VESA 100 x 100 |
| Panel cut | - |

Optionals

| | |
|--------------|--|
| Screen | High brightness for outdoors use |
| USB Ports | 4 x USB 2.0 |
| Serial Ports | 2 x RS-232 / 2 x RS-232/422/485 |
| Modem | 3G / LTE + GPS |
| WIFI Module | Wifi 2,4GHz / Wifi 2,4GHz i 5GHz + Bluetooth |
| Slot PCIe | To Be Consulted |
| Others | To Be Consulted |

Protection / Environmental Conditions

| | |
|----------------------------|----------------|
| IP & Material | Aluminum Front |
| °C Operation | 0° a 60° C |
| °C Storage | -10° a 70° C |
| Humidity (no condensation) | 0% - 95% |

Power Supply

| | |
|------------------------|---|
| Input Voltage | 9-24Vdc (External power supply) 110-220Vac/12Vdc) |
| Optional Input Voltage | 24Vdc |