



- Intel® Core™ i7-6700TE 2,40 GHz
- 27" Projected Capacitive Multitouch Display (PCAP)
- Aluminum
- Made in Spain
- Compact design



Intel®
Processors



Touch
Technology



Efficient Power
Consumption




Double
Display

CPU boards with latest generation Intel® Processors, fanless, low power consumption and exceptional performance.
Manufactured in Aluminium.
Projected Capacitive Multitouch sensor (PCAP).



Dimensions



Specifications

| Display | |
|------------------|--|
| Touch technology | Projected Capacitive MultiTouch (PCAP) |
| Inches | 27" |
| Format | 16:9 |
| Resolution | 1920 x 1080 |
| Backlight | LED |
| Brightness | 350 cd/m2 |
| Ratio contrast | 3000:1 |
| Angle vision | 178/178 |
| LED Life Time | 30.000 h |

| System | |
|------------|--|
| CPU | Intel® Core™ i7-6700TE (6th Generation) 2,40 GHz |
| Memory | 2Gb Scalable to 32Gb |
| Hard Drive | 60/120/240GB SSD. 500GB/1TB SATA. |
| Graphics | Intel® Gen9 Intel® Graphics DX 11/12 |
| Chipset | Intel® H110 |
| OS | Win7 Pro / Win7 Embedded / Win10 Pro / Win10 IoT Enterprise / Linux |

| Input / Output | |
|----------------|-----------------------------------|
| USB Ports | 4 x USB 3.0 |
| Serial Ports | - |
| Ethernet | 2 x Intel® Giga Ethernet |
| Video | 2 x HDMI |
| Audio | 1 x Audio output / 1 x Microphone |
| Expansión | 2 x Mini-PCIe / 1 x PCIe4 |

| Mechanical | |
|------------|-------------------|
| Dimensions | 671 x 409 x 85 mm |
| Weight | 13 kg |
| Mount | VESA 200 x 200 |
| Panel cut | - |

| Optionals | |
|--------------|---|
| Screen | High brightness for outdoors use |
| USB Ports | 4 x USB 2.0 |
| Serial Ports | 2 x RS-232 / 2 x RS-232/422/485 |
| Modem | 3G / LTE + GPS |
| WIFI Module | Wifi 2,4GHz / Wifi 2,4GHz i 5GHz + Bluetooth |
| Slot PCIe | To Be Consulted |
| Others | To Be Consulted |

| Protection / Environmental Conditions | |
|---------------------------------------|------------------------------------|
| IP & Material | Double Height Aluminum Front Panel |
| °C Operation | 0° a 60° C |
| °C Storage | -10° a 70° C |
| Humidity (no condensation) | 0% - 95% |

| Power Supply | |
|------------------------|--|
| Input Voltage | 12Vdc/19-24Vdc (External power supply 110-220Vac/12Vdc) |
| Optional Input Voltage | - |