

IRTCTH430SC3CFA

NERO - Closed Frame Panel PC + ThinClind

OS



- RockChip RK3588 OctaCore Cortex-A76+A55 1,8GHz
- 43" Projected Capacitive Multitouch Display (PCAP)
- Painted Metal sheet
- IP65 Front Protection
- Fanless Compact design
- Made in Spain











ARM® Processors

Touch Technology

Efficient Power Consumption

Double Display

IP65 Front Protection

CPU boards with latest generation Intel® Processors, fanless, low power consumption and exceptional performance.

Manufactured in painted sheet metal with IP65 protection.

5-Wire Resistive or Projected Capacitive Multitouch sensor (PCAP).








Dimensions



IRTCTH430SC3CFA

NERO - Closed Frame Panel PC + ThinClind OS





IRTCTH430SC3CFA

NERO - Closed Frame Panel PC + ThinClind

OS

Specifications

Display	
Touch technology	Projected Capacitive MultiTouch (PCAP)
Format	16:9
Resolution	1920 x 1080
Backlight	LED
Brightness	500 cd/m2
Ratio contrast	4000:1
Angle vision	178/178
LED Life Time	60.000 h

Optionals	
Screen	High brightness for outdoors use
USB Ports	-
Serial Ports	-
Modem	-
WIFI Module	-
Slot PCIe	To Be Consulted
Others	To Be Consulted

System	
CPU	RockChip RK3588 OctaCore Cortex- A76+A55 1,8GHz
Memory	4GB On Board
Hard Drive	32GB on Board (Upgradable with 2242 NVMe SSD)
Graphics	Mali G61 MP4
Chipset	RK3588 Onboard (SoC)
OS	Linux/ThinClind OS

Protection /	Environmental Conditions
IP & Material	IP65 Painted Metal Plate Front
°C Operation	0° a 60° C
°C Storage	-10° a 70° C
Humidity (no condensation)	0% - 95%

Input / Ouput	
USB Ports	2 x USB 2.0
Serial Ports	
Ethernet	2 x Realtek Gigabit Ethernet
Video	1 x HDMI
Audio	1 x Salida audio
Expansión	

Power Supply	
Input Voltage	12Vdc (External power supply 110-220Vac/12Vdc)
Optional Input Voltage	-