

IRTMWP150SJNDA

HYDRA-M - Full IP65 Industrial Monitor



- .
- 15" FLAT 5-Wire Resistive Touch Display
- Stainless Steel 316L
- IP66 Full Protection
- Compact design
- Made in Spain



Touch Technology



Efficient Power Consumption



Double Display



IP66 Full Enclosure

Manufactured in 316L Stainless Steel with Full IP66 enclosure.

5-Wire Resistive or Projected Capacitive Multitouch sensor (PCAP).










Dimensions







IRTMWP150SJNDA

HYDRA-M - Full IP65 Industrial Monitor

Specifications

Display	
Touch technology	FLAT 5-Wire Resistive
Inches	15"
Format	4:3
Resolution	1024 x 768
Backlight	LED
Brightness	300 cd/m2
Ratio contrast	2000:1
Angle vision	176/176
LED Life Time	70.000 h

Optionals	
Screen	High brightness for outdoors use
USB Ports	Optional
Serial Ports	-
Modem	-
WIFI Module	-
Slot PCIe	-
Others	-

System		
CPU	-	
Memory	-	
Hard Drive	-	
Graphics	-	
Chipset	-	
OS	-	

Protection / Environmental Conditions		
IP & Material	Full IP66 Stainless Steel 316L	
°C Operation	0° a 60° C TBC: -20° a 60° C (Atom)	
°C Storage	-10° a 70° C TBC: -20° a 70° (Atom)	
Humidity (no condensation)	0% a 95%	

Input / Ouput	
USB Ports	1 x USB (Touch Controller)
Serial Ports	-
Ethernet	-
Video	1 x HDMI
Audio	-
Expansión	-

Power Supply	
Input Voltage	12Vdc (External power supply 110-220Vac/12Vdc)
Optional Input Voltage	12-36Vdc