



- Intel® N97™ Quad Core 3,60 GHz
- 15" 5-Wire Resistive Touch Display FLAT
- Anodized Aluminum
- IP66 Front Protection
- Fanless compact design
- Made in Spain



CPU boards with latest generation Intel® Processors, fanless, low power consumption and exceptional performance.  
IP66 Front Bezel protection, available in Anodized Aluminum or Stainless Steel.  
5-Wire Resistive or Projected Capacitive Multitouch sensor (PCAP).



### Dimensions



### Specifications

| Display          |                       |
|------------------|-----------------------|
| Touch technology | FLAT 5-Wire Resistive |
| Inches           | 15"                   |
| Format           | 4:3                   |
| Resolution       | 1024 x 768            |
| Backlight        | LED                   |

| System     |  |
|------------|--|
| CPU        | Intel® N97™ Quad Core 3,60 GHz                 |
| Memory     | DDR5 4Gb Scalable to 16Gb                      |
| Hard Drive | 60/120/240/480Gb SSD. 500Gb/1Tb SATA.          |
| Graphics   | Intel® UHD Graphics                            |
| Chipset    | N97 Onboard (SoC)                              |
| OS         | Win10/11 Pro / Win10/11 IoT Enterprise / Linux |

| Input / Ouput |   |
|---------------|---|
| USB Ports     | 1 x USB 3.2 (Gen.2) Type-A, 1 x USB 3.2 (Gen.2) Type-C, 4 x USB 2.0 |
| Serial Ports  | -   |
| Ethernet      | 2 x Intel® Giga Ethernet  |
| Video         | 2 x HDMI  |
| Audio         | 1 x Audio output / 1 x Microphone                                   |
| Expansión     | 1 x M.2 2230 E key, 1 x M.2 3042/3052 B key                         |

| Optionals    |  |
|--------------|--|
| USB Ports    | 4 x USB 2.0                                  |
| Serial Ports | 5 x RS-232 / 1 x RS-232/422/485              |
| Modem        | 3G / LTE + GPS                               |
| WIFI Module  | Wifi 2,4GHz / Wifi 2,4GHz i 5GHz + Bluetooth |
| Slot PCIe    | To Be Consulted                              |
| Others       | To Be Consulted                              |

| Protection / Environmental Conditions |  |
|---------------------------------------|--|
| IP & Material                         | IP66 Anodized Aluminum Front Bezel     |
| °C Operation                          | 0° a 60° C<br>TBC: -20° a 60° C (Atom) |
| °C Storage                            | -10° a 70° C<br>TBC: -20° a 70° (Atom) |
| Humidity (no condensation)            | 0% a 95%                               |

| Power Supply           |                                   |
|------------------------|-----------------------------------|
| Input Voltage          | 9-28Vdc (External 110-220V/12Vdc) |
| Optional Input Voltage | -                                 |