



- Intel® Core™ i5-9500TE 3,00 GHz
- 18.5" 5-Wire Resistive Touch Display
- Anodized Aluminum
- IP65 Front Protection
- Compact design
- Made in Spain




CPU boards with latest generation Intel® Processors, fanless, low power consumption and exceptional performance.

IP65 Front Bezel protection, available in Anodized Aluminum or Stainless Steel.

5-Wire Resistive or Projected Capacitive Multitouch sensor (PCAP).



Dimensions



Specifications

Display

| | |
|------------------|------------------|
| Touch technology | 5-Wire Resistive |
| Inches | 18,5" |
| Format | 16:9 |
| Resolution | 1920 x 1080 |
| Backlight | LED |
| Brightness | 1000 cd/m2 |
| Ratio contrast | 1000:1 |
| Angle vision | 178/178 |
| LED Life Time | 50.000 h |

System

| | |
|------------|--|
| CPU | Intel® Core™ i5-9500E (9th Generation) 3,00 GHz |
| Memory | DDR4 2Gb Scalable to 32Gb |
| Hard Drive | 60/120/240Gb SSD. 500Gb/1Tb SATA. |
| Graphics | Intel® HD Graphics |
| Chipset | Intel® Coffee Lake-S H310 |
| OS | Win10 Pro / Win10 IoT Enterprise / Linux |

Input / Ouput

| | |
|--------------|-----------------------------------|
| USB Ports | 4 x USB 3.0 |
| Serial Ports | - |
| Ethernet | 2 x Intel® Giga Ethernet |
| Video | 1 x VGA / 1 x HDMI |
| Audio | 1 x Audio output / 1 x Microphone |
| Expansión | 1 x PCIe4 / 2 x M.2(2230/2242) |

Mechanical

| | |
|------------|-------------------|
| Dimensions | 501 x 326 x 92 mm |
| Weight | 10 kg |
| Mount | Wall-Mount |
| Panel cut | 458 x 282 mm |

Optionals

| | |
|-------------|--|
| Screen | High brightness for outdoors use |
| USB Ports | 5 x USB 2.0 |
| Modem | 3G / LTE + GPS |
| WIFI Module | Wifi 2,4GHz / Wifi 2,4GHz i 5GHz + Bluetooth |
| Slot PCIe | To Be Consulted |
| Others | To Be Consulted |

Protection / Environmental Conditions

| | |
|----------------------------|--|
| IP & Material | IP65 Anodized Aluminum Front Bezel |
| °C Operation | 0° a 60° C TBC: -20° a 60° C (Atom) |
| °C Storage | -10° a 70° C TBC: -20° a 70° (Atom) |
| Humidity (no condensation) | 0% a 95% |

Power Supply

| | |
|------------------------|--|
| Input Voltage | 12Vdc/19-24Vdc (External power supply 110-220Vac/12Vdc) |
| Optional Input Voltage | - |