



- Intel® Core™ i5-1135G7 2,4Ghz
- 15.6" Projected Capacitive Multitouch Display (PCAP)
- Stainless Steel 316L
- IP66 Full Protection
- Fanless compact design
- Made in Spain



Intel®  
Processors



Touch  
Technology



Efficient Power  
Consumption



Double  
Display



IP66 Full  
Enclosure


CPU boards with latest generation Intel® Processors, fanless, low power consumption and exceptional performance.

Manufactured in 316L Stainless Steel with full IP66 enclosure. Selection and configuration up to five ports, among COM (serial), USB or Ethernet ports, through IP69 connectors.

5-Wire Resistive or Projected Capacitive Multitouch sensor (PCAP).



### Dimensions



### Specifications

#### Display

|                  |                                        |
|------------------|----------------------------------------|
| Touch technology | Projected Capacitive MultiTouch (PCAP) |
| Inches           | 15,6"                                  |
| Format           | 16:9                                   |
| Resolution       | 1920 x 1080                            |
| Backlight        | LED                                    |
| Brightness       | 450 cd/m2                              |
| Ratio contrast   | 800:1                                  |
| Angle vision     | 160/160                                |
| LED Life Time    | 50.000 h                               |

#### System

|            |                                                 |
|------------|-------------------------------------------------|
| CPU        | Intel® Core™ i5-1135G7 (11th Generation) 2,4Ghz |
| Memory     | DDR4 2Gb Scalable a 64Gb                        |
| Hard Drive | 120/240/480Gb SSD M.2 NVMe. 500Gb/1Tb SATA.     |
| Graphics   | Intel® HD Graphics                              |
| Chipset    | Intel® Tiger Lake i5-1135G7 SoC                 |
| OS         | Win10 Pro / Win10 IoT Enterprise / Linux        |

#### Input / Output

|              |                                                              |
|--------------|--------------------------------------------------------------|
| USB Ports    | 4 x USB3.2 (Gen.2)                                           |
| Serial Ports | -                                                            |
| Ethernet     | 2 x Intel® Giga Ethernet                                     |
| Video        | 2 x HDMI / 2 x DP                                            |
| Audio        | 1 x Audio output / 1 x Microphone                            |
| Expansión    | 1 x M.2 E-key (2230) USB2.0 / PCIe x1 interface support CNVi |

#### Optionals

|              |                                              |
|--------------|----------------------------------------------|
| Screen       | High brightness for outdoors use             |
| USB Ports    | 4 x USB 2.0                                  |
| Serial Ports | 2 x RS-232 / 2 x RS-232/422/485              |
| Modem        | 3G / LTE + GPS                               |
| WIFI Module  | Wifi 2,4GHz / Wifi 2,4GHz i 5GHz + Bluetooth |
| Slot PCIe    | To Be Consulted                              |
| Others       | To Be Consulted                              |

#### Protection / Environmental Conditions

|                            |                                          |
|----------------------------|------------------------------------------|
| °C Operation               | 0° a 60° C<br>TBC: -20° a 60° C (Atom)   |
| °C Storage                 | -10° a 70° C<br>TBC: -20° a 70° C (Atom) |
| Humidity (no condensation) | 0% a 95%                                 |

#### Power Supply

|                        |                                                    |
|------------------------|----------------------------------------------------|
| Input Voltage          | 9-24Vdc (External power supply) a 110-220Vac/12Vdc |
| Optional Input Voltage | 24Vdc                                              |