




- Intel® Celeron™ J6412 Quad Core 2,00 GHz
- 17" Projected Capacitive Multitouch Display (PCAP)
- Stainless Steel 316L
- IP65 Full Protection
- Fanless compact design
- Made in Spain



CPU boards with latest generation Intel® Processors, fanless, low power consumption and exceptional performance. Manufactured in 316L Stainless Steel with full IP65 enclosure. Selection and configuration up to five ports, among COM (serial), USB or Ethernet ports, through IP68 connectors. 5-Wire Resistive or Projected Capacitive Multitouch sensor (PCAP).



Dimensions



Specifications

Display

| | |
|------------------|--|
| Touch technology | Projected Capacitive MultiTouch (PCAP) |
| Inches | 17" |
| Format | 5:4 |
| Resolution | 1280 x 1024 |
| Backlight | LED |
| Brightness | 1600 cd/m2 |
| Ratio contrast | 1000:1 |
| Angle vision | 170/160 |
| LED Life Time | 50.000 h |

System

| | |
|------------|--|
| CPU | Intel® Celeron™ J6412 Quad Core 2,00 GHz |
| Memory | DDR4 2Gb Scalable to 16Gb |
| Hard Drive | 60/120/240/480Gb SSD. 500Gb/1Tb SATA. |
| Graphics | Intel® HD Graphics |
| Chipset | J6412 Onboard (SoC) |
| OS | Win10 Pro / Win10 IoT Enterprise / Linux |

Input / Ouput

| | |
|--------------|--|
| USB Ports | 4 x USB 2.0 / 3 x USB 3.1 |
| Serial Ports | - |
| Ethernet | 1 x Realtek Giga Ethernet |
| Video | 1 x HDMI |
| Audio | 1 x Audio output / 1 x Microphone |
| Expansión | 1 x M.2 (2242/2260) / 1 x M.2 (2230) / 1 x M.2 (3042/3052) |

Mechanical

| | |
|------------|-------------------|
| Dimensions | 452 x 421 x 60 mm |
| Weight | 10 kg |
| Mount | VESA 100 x 100 |
| Panel cut | - |

Optionals

| | |
|--------------|--|
| Screen | High brightness for outdoors use |
| USB Ports | 3 x USB 2.0 |
| Serial Ports | 4 x RS-232 / 2 x RS-232/422/485 |
| Modem | 3G / LTE + GPS |
| WIFI Module | Wifi 2,4GHz / Wifi 2,4GHz i 5GHz + Bluetooth |
| Slot PCIe | To Be Consulted |
| Others | To Be Consulted |

Protection / Environmental Conditions

| | |
|----------------------------|--|
| IP & Material | Full IP65 Stainless Steel 316L |
| °C Operation | 0° a 60° C TBC: -20° a 60° C (Atom) |
| °C Storage | -10° a 70° C TBC: -20° a 70° (Atom) |
| Humidity (no condensation) | 0% a 95% |

Power Supply

| | |
|------------------------|--|
| Input Voltage | 12Vdc (External power supply 110-220Vac/12Vdc) |
| Optional Input Voltage | - |