




- Intel® Core™ i5-1145G7e 2,4Ghz
- 42" Projected Capacitive Multitouch Display (PCAP)
- Stainless Steel 316L
- IP66 Full Protection
- Fanless compact design
- Made in Spain



CPU boards with latest generation Intel® Processors, fanless, low power consumption and exceptional performance.  
 Manufactured in 316L Stainless Steel with full IP66 enclosure. Selection and configuration up to five ports, among COM (serial), USB or Ethernet ports, through IP69 connectors.  
 5-Wire Resistive or Projected Capacitive Multitouch sensor (PCAP).



### Dimensions



### Specifications

| Display          |  |
|------------------|--|
| Touch technology | Projected Capacitive MultiTouch (PCAP) |
| Inches           | 42"                                    |
| Format           | 16:9                                   |
| Resolution       | 1920 x 1080                            |
| Backlight        | LED                                    |
| Brightness       | 500 cd/m2                              |
| Ratio contrast   | 4000:1                                 |
| Angle vision     | 178/178                                |
| LED Life Time    | 60.000 h                               |

| System     |  |
|------------|--|
| CPU        | Intel® Core™ i5-1145G7e (11th Generation) 2,4Ghz |
| Memory     | DDR4 2Gb Scalable a 64Gb                         |
| Hard Drive | 120/240/480Gb SSD M.2 NVMe. 500Gb/1Tb SATA.      |
| Graphics   | Intel® HD Graphics                               |
| Chipset    | Intel® Tiger Lake i5-1135G7 SoC                  |
| OS         | Win10 Pro / Win10 IoT Enterprise / Linux         |

| Input / Ouput |  |
|---------------|--|
| USB Ports     | 4 x USB3.2 (Gen.2)   |
| Serial Ports  | -  |
| Ethernet      | 2 x Intel® Giga Ethernet                                   |
| Video         | 2 x HDMI / 2 x DP  |
| Audio         | 1 x Audio output / 1 x Microphone                          |
| Expansión     | 1 x M.2 E-key (2230) USB2.0 / PCIe1 interface support CNVi |

| Mechanical |                    |
|------------|--------------------|
| Dimensions | 1075 x 684 x 60 mm |
| Weight     | 30 kg              |
| Mount      | VESA 400 x 400     |
| Panel cut  | -                  |

| Optionals    |  |
|--------------|--|
| Screen       | High brightness for outdoors use             |
| USB Ports    | 4 x USB 2.0                                  |
| Serial Ports | 2 x RS-232 / 2 x RS-232/422/485              |
| Modem        | 3G / LTE + GPS                               |
| WIFI Module  | Wifi 2,4GHz / Wifi 2,4GHz i 5GHz + Bluetooth |
| Slot PCIe    | To Be Consulted                              |
| Others       | To Be Consulted                              |

| Protection / Environmental Conditions |  |
|---------------------------------------|--|
| IP & Material                         | Full IP66 Stainless Steel 316L         |
| °C Operation                          | 0° a 60° C<br>TBC: -20° a 60° C (Atom) |
| °C Storage                            | -10° a 70° C<br>TBC: -20° a 70° (Atom) |
| Humidity (no condensation)            | 0% a 95%                               |

| Power Supply           |  |
|------------------------|--|
| Input Voltage          | 9-24Vdc (External power supply)<br>110-220Vac/12Vdc) |
| Optional Input Voltage | 24Vdc  |