



- Intel® Core™ i3-6100TE 2,70 GHz
- 15,6" 5-Wire Resistive Touch Display
- Painted metal sheet
- IP65 Front Protection
- Compact design
- Made in Spain



Intel®  
Processors



Touch  
Technology



Efficient Power  
Consumption



Double  
Display



IP65 Front  
Protection


CPU boards with latest generation Intel® Processors, fanless, low power consumption and exceptional performance.

Manufactured in painted sheet metal with IP65 protection.

5-Wire Resistive or Projected Capacitive Multitouch sensor (PCAP).



### Dimensions



### Specifications

#### Display

|                  |                  |
|------------------|------------------|
| Touch technology | 5-Wire Resistive |
| Inches           | 18,5"            |
| Format           | 16:9             |
| Resolution       | 1366 x 768       |
| Backlight        | LED              |
| Brightness       | 450 cd/m2        |
| Ratio contrast   | 1000:1           |
| Angle vision     | 170/160          |
| LED Life Time    | 50.000 h         |

#### System

|            |                                                     |
|------------|-----------------------------------------------------|
| CPU        | Intel® Core™ i3-6100TE (6th Generation)<br>2,70 GHz |
| Memory     | 2Gb Scalable to 32Gb                                |
| Hard Drive | 60/120/240GB SSD. 500GB/1TB SATA.                   |
| Graphics   | Intel® Gen9 Intel® Graphics DX 11/12                |
| Chipset    | Intel® H110                                         |
| OS         | Win10 Pro / Win10 IoT Enterprise / Linux            |

#### Input / Ouput

|              |                                   |
|--------------|-----------------------------------|
| USB Ports    | 4 x USB 3.0                       |
| Serial Ports | -                                 |
| Ethernet     | 2 x Intel® Giga Ethernet          |
| Video        | 2 x HDMI                          |
| Audio        | 1 x Audio output / 1 x Microphone |
| Expansión    | 2 x Mini-PCIe / 1 x PCIe x4       |

#### Mechanical

|            |                   |
|------------|-------------------|
| Dimensions | 491 x 309 x 86 mm |
| Weight     | 7,7 kg            |
| Mount      | VESA 100 x 100    |
| Panel cut  | -                 |

#### Optionals

|              |                                              |
|--------------|----------------------------------------------|
| Screen       | High brightness for outdoors use             |
| USB Ports    | 4 x USB 2.0                                  |
| Serial Ports | 2 x RS-232 / 2 x RS-232/422/485              |
| Modem        | 3G / LTE + GPS                               |
| WIFI Module  | Wifi 2,4GHz / Wifi 2,4GHz i 5GHz + Bluetooth |
| Slot PCIe    | To Be Consulted                              |
| Others       | To Be Consulted                              |

#### Protection / Environmental Conditions

|                            |                                                     |
|----------------------------|-----------------------------------------------------|
| IP & Material              | IP65 Front of Painted Sheet Metal and Double Height |
| °C Operation               | 0° a 60° C                                          |
| °C Storage                 | -10° a 70° C                                        |
| Humidity (no condensation) | 0% - 95%                                            |

#### Power Supply

|                        |                                                         |
|------------------------|---------------------------------------------------------|
| Input Voltage          | 12Vdc/19-24Vdc (External power supply 110-220Vac/12Vdc) |
| Optional Input Voltage | -                                                       |