



- Intel® Celeron™ J3455 Quad Core 2,30 GHz
- 18.5" Projected Capacitive Multitouch Display (PCAP)
- Aluminum
- Made in Spain
- Fanless compact design



Intel®  
Processors



Touch  
Technology



Efficient Power  
Consumption




Double  
Display

CPU boards with latest generation Intel® Processors, fanless, low power consumption and exceptional performance.  
Manufactured in Aluminium.  
Projected Capacitive Multitouch sensor (PCAP).



### Dimensions



### Specifications

#### Display

|                  |                                        |
|------------------|----------------------------------------|
| Touch technology | Projected Capacitive MultiTouch (PCAP) |
| Inches           | 18,5"                                  |
| Format           | 16:9                                   |
| Resolution       | 1366 x 768                             |
| Backlight        | LED                                    |
| Brightness       | 450 cd/m2                              |
| Ratio contrast   | 1000:1                                 |
| Angle vision     | 170/160                                |
| LED Life Time    | 50.000 h                               |

#### System

|            |                                          |
|------------|------------------------------------------|
| CPU        | Intel® Celeron™ J3455 Quad Core 2,30 GHz |
| Memory     | DDR3L 2Gb Scalable to 8Gb                |
| Hard Drive | 60/120/240GB SSD. 500GB/1TB SATA.        |
| Graphics   | Intel® HD Graphics                       |
| Chipset    | J3455 Onboard (SoC)                      |
| OS         | Win10 Pro / Win10 IoT Enterprise / Linux |

#### Input / Ouput

|              |                                            |
|--------------|--------------------------------------------|
| USB Ports    | 4 x USB 3.0                                |
| Serial Ports | -                                          |
| Ethernet     | 1 x Realtek Giga Ethernet                  |
| Video        | 2 x HDMI                                   |
| Audio        | 1 x Audio output                           |
| Expansión    | 1 x Mini-PCle / 1 x M.2(2242/2260) for SSD |

#### Mechanical

|            |                   |
|------------|-------------------|
| Dimensions | 461 x 281 x 55 mm |
| Weight     | 5,3 kg            |
| Mount      | VESA 100 x 100    |
| Panel cut  | -                 |

#### Optionals

|              |                                              |
|--------------|----------------------------------------------|
| Screen       | High brightness for outdoors use             |
| USB Ports    | 2 x USB 2.0                                  |
| Serial Ports | 2 x RS-232/422/485                           |
| Modem        | 3G / LTE + GPS                               |
| WIFI Module  | Wifi 2,4GHz / Wifi 2,4GHz i 5GHz + Bluetooth |
| Slot PCIe    | To Be Consulted                              |
| Others       | To Be Consulted                              |

#### Protection / Environmental Conditions

|                            |                |
|----------------------------|----------------|
| IP & Material              | Aluminum Front |
| °C Operation               | 0° a 60° C     |
| °C Storage                 | -10° a 70° C   |
| Humidity (no condensation) | 0% - 95%       |

#### Power Supply

|                        |                                                |
|------------------------|------------------------------------------------|
| Input Voltage          | 12Vdc (External power supply 110-220Vac/12Vdc) |
| Optional Input Voltage | 24Vdc                                          |