

IRTMWP150SCNDA

Full IP65 Industrial Monitor



- •
- 15" Projected Capacitive Multitouch Display (PCAP)
- Stainless Steel 316L
- IP65 Full Protection
- Compact design
- Made in Spain



Touch Technology







Efficient Power gy Consumption

e /

IP65 Full Enclosure

Manufactured in 316L Stainless Steel with Full IP65 enclosure.

5-Wire Resistive or Projected Capacitive Multitouch sensor (PCAP).










Dimensions







IRTMWP150SCNDA

Full IP65 Industrial Monitor

Specifications

Display	
Touch technology	Projected Capacitive MultiTouch (PCAP)
Inches	15"
Format	4:3
Resolution	1024 x 768
Backlight	LED
Brightness	300 cd/m2
Ratio contrast	2000:1
Angle vision	176/176
LED Life Time	70.000 h

System			
CPU	-		
Memory	-		
Hard Drive	-		
Graphics	-		
Chipset	-		
OS	-		

Input / Ouput		
USB Ports	1 x USB (Touch Controller)	
Serial Ports	-	
Ethernet		
Video	1 x HDMI	
Audio		
Expansión		

Optionals		
Screen	High brightness for outdoors use	
USB Ports	Optional	
Serial Ports	-	
Modem	-	
WIFI Module	-	
Slot PCle	-	
Others	-	

Protection / Environmental Conditions			
IP & Material	Full IP65 Stainless Steel 316L		
°C Operation	0° a 60° C TBC: -20° a 60° C (Atom)		
°C Storage	-10° a 70° C TBC: -20° a 70° (Atom)		
Humidity (no condensation)	0% a 95%		

Power Supply		
Input Voltage	12Vdc (External power supply 110-220Vac/12Vdc)	
Optional Input Voltage	12-36Vdc	